

NOTES:

- 1. VALVE BOX MUST BE TRAFFIC RATED (CHRISTY G-5, AS APPROVED BY WATER UTILITY) WITH CAST IRON LID OR EQUAL.
- 2. MINIMUM OF 10 INCHES INSIDE DIAMETER.
- 3. CAST IRON LID MARKED "WATER" FOR WATER LINE APPLICATIONS. CAST IRON LID MARKED "RECLAIMED WATER" OR "RCW" WHEN INSTALLED ON A RECLAIMED WATER MAIN. CAST IRON LID SHALL BE MARKED "SS FORCE MAIN" OR "SS FM" WHEN INSTALLED ON A SANITARY SEWER FORCE MAIN.
- 4. RISER OF 8 INCHES PVC EXTENDED IN VALVE CAN A MINIMUM OF 6 INCHES.
- 5. ALL NEW VALVE BOXES TO BE SET TO GRADE PER "VALVE" DETAIL B10.
- 6. TORQUE GRADE RING BOLTS TO MANUFACTURER'S RECOMMENDATIONS.

PAGE 1 OF 1

NO.	REVISION	DATE	STANDARD DETAIL FOR PUBLIC WORKS CONSTRUCTION	DOU	SLAS COUNTY
			VALVE BOX	DATE:	JULY 2017
				DWG:	B11