

SEE NOTES ON PAGE 2

PAGE 1 OF 2

NO.	REVISION	DATE	STANDARD DETAIL FOR PUBLIC WORKS CONSTRUCTION	SECTIO		
			1 ••	DOUGLAS COUNTY		
			1 ½" - 2" METER SET	DATE:	JULY 2017	
				DWG:		
			WILTER SET		B05	

NOTES AND PARTS KEY:

- 1. USE A TRAFFIC RATED LID AND BOX WITH READING LID IN ALL TRAFFIC AREAS.
- 2. METER SHALL BE INSTALLED SO AS TO ACHIEVE A WATER TIGHT SEAL.
- 3. CUT TWO PIECES OF 1 INCH PIPE 18 INCHES LONG AND INSTALL THROUGH THE BRACE EYE SUPPORTS.
- 4. SINGLE METER GASKET.
- 5. FLANGED ANGLE BALL CHECK VALVE.
- 6. WATER METER AND RADIO READ HARDWARE AS APPROVED BY WATER UTILITY. (KGID DOES NOT SUPPLY WATER METER).
- 7. BRACE EYE SUPPORTS.
- 8. BY-PASS BALL VALVE WITH LOCKABLE CAP.
- 9. POLYETHYLENE TUBING (SIZE AS REQUIRED BY WATER UTILITY). MINIMUM TEST 200 PSI.
- 10.4" THICK MUELLER INSULATION PAD OR 4' X 4' BLANKET INSULATION TO BE INSTALLED ABOVE METER AND BELOW TRANSMITTER.

PAGE 2 OF 2

NO.	REVISION	DATE	I STANDARD BETALE FOR FOREIG WORKS GORSTROOTION	SECTION:	
			I	DOUGL	AS COUNTY
			$1 \frac{1}{2}$ " - 2"	DATE:	ULY 2017
			METER SET	DWG:	B05
					603